

## PRODUCT

### SKU/Color Names :

|                      |                    |
|----------------------|--------------------|
| AT-02 Mile High      | AT-17 Myrtle Beach |
| AT-03 Venice Beach   | AT-18 Islamorada   |
| AT-04 Rehoboth       | AT-19 Amelia       |
| AT-05 Antigua        | AT-20 Whitehaven   |
| AT-07 Wildwood Crest | AT-21 Blue Sands   |
| AT-12 Oakwood        | AT-22 Loreda       |
| AT-13 Cannes         | AT-24 Santorini    |
| AT-14 Biscayne       | AT-25 Mancora      |
| AT-15 Galway         | AT-26 Palomino     |
| AT-16 Brighton       | AT-27 Captiva      |

### Construction :

- 4mm Rigid Core (Stone and Virgin DOTP Composite)
- 1mm IXPE attached cushion (No VOCs)
- 5 unique planks per pattern, 10 with a flip

### Wear Layer :

20mil with Quantum X™ Technology Finish  
(Proposition 65 Compliant)

### Installation :

- Click, Unilin Locking System
- Float or Glue Down
- 50 LF before transition needed
- Matching Accessories: 3-in-1 Molding, Flush Stair Nose
- Use Polyurethane for wet spaces. Pressure sensitive adhesive is acceptable for other areas. Please reference our installation instructions for further details or contact [sales@duratousa.com](mailto:sales@duratousa.com)

\* A 50'x50' install requires 10mm expansion space along walls in uncontrolled environments (such as no HVAC).

\* Do not install below 50°F, 24-hr acclimation time.

\* Use a floor mat for furniture utilizing castor wheels.

## SIZE/PACKAGING

Plank Size : 7.2" x 48"

Planks/Carton : 10 Sq. Ft./Carton : 24.028

Cartons/Pallet : 55 Sq. Ft./Pallet : 1321.54

Sq. Ft./Container : 26,430.80

## FEATURES



ANTI-MICROBIAL



WATERPROOF



FIRE RESISTANT



PET FRIENDLY



INDENT RESISTANT



**LIGHT COMMERCIAL USE**  
Durable enough to withstand everyday foot traffic.



**QUANTUM X™ TECHNOLOGY**  
Industry-leading resistance to scratches, stains and dents, strengthened by real titanium.

## TEST DATA

ASTM E492-09  
Impact Sound Conduction  
&  
ASTM E90-09  
Airborne Sound Conduction

6"slab, no drop ceiling:  
STC 53 db / IIC 55 db

OSB subfloor with fiberglass and open truss using standard resilient channel with fastened gypsum board:  
STC 58 / IIC 55 / IIC 66

\* Sound test scores are relative to varying conditions. For accurate results, contact Durato for on-site testing and/or specific buildouts.

ASTM D2394  
Slip Resistance DCOF  
(Sliding)

Wet: Manufacturing Direction 0.63  
Wet: Across-Manufacturing Direction 0.72  
Dry: Manufacturing Direction 0.58  
Dry: Across-Manufacturing Direction 0.60

ASTM D2394  
Slip Resistance SCOF  
(Static)

Wet: Manufacturing Direction 0.72  
Wet: Across-Manufacturing Direction 0.78  
Dry: Manufacturing Direction 0.59  
Dry: Across-Manufacturing Direction 0.70

ASTM D1037  
Dynamic Load Limit

1,162 psi

ASTM F970-22  
Static Load Limit

Passes, 0.35mm indent, 250 psi

ASTM F1914-18  
Residual Indentation

Meets or Exceeds, average 0.09mm

ASTM F2199-20  
Dimensional Stability

Meets or Exceeds

ASTM E648  
Critical Radiant Flux

Meets or Exceeds, Class 1 (>1.10)

ASTM F1514-19  
Resistance to Heat

Meets or Exceeds, average  $\Delta E^*$  0.80

ASTM F1515-21  
Resistance to Light

Meets or Exceeds, average  $\Delta E^*$  1.72

ASTM F925-13  
Resistance to Chemicals

No change, Not affected

ASTM C518  
Thermal Resistance

R Value -0.6

## WARRANTY



LIMITED RESIDENTIAL  
WARRANTY



LIMITED LIGHT  
COMMERCIAL WARRANTY

