

### PRODUCT

#### SKU/Color Names :

DRWD-01 Willow	DRWD-06 Cypress
DRWD-02 Rowan	DRWD-07 Balsa
DRWD-03 Mulberry	DRWD-08 Alder
DRWD-04 Laurel	DRWD-09 Teak
DRWD-05 Hawthorn	DRWD-10 Tamarind

#### Construction :

- 8mm Core
- 1.5mm IXPE attached cushion (No VOCs)
- 14 unique planks per pattern, 7 with a flip

#### Wear Layer :

AC4+ with Diamante X™ Technology Finish  
(Proposition 65 Compliant)

#### Installation :

- Click, Unilin Locking System
- Float or Glue Down
- 55 LF before transition needed
- Matching Accessories: RD and TM Molding, Flush Stair Nose
- Not acceptable for wet spaces. Pressure sensitive adhesive is acceptable. Please reference our installation instructions for further details or contact [sales@duratousa.com](mailto:sales@duratousa.com)

\*A 50'x50' install requires 10mm expansion space along walls.

\*Do not install below 50°F, 24-hr acclimation time.

\* Use a floor mat for office chairs.

### SIZE/PACKAGING

Plank Size : 6.50" x 47.83"

Planks/Carton : 9 Sq. Ft./Carton : 19.42

Cartons/Pallet : 66 Sq. Ft./Pallet : 1,281.72

Sq. Ft./Container : 25,634.40

### FEATURES



ANTI-MICROBIAL



WATER RESISTANT



FIRE RESISTANT



PET FRIENDLY



INDENT RESISTANT



#### AUTHENTEX™ FINISH

High-definition imagery plus and Embossed in Register creates an authentic wood look and texture.



#### DIAMANTE X™ TECHNOLOGY

Industry-leading resistance to scratches, stains and dents, strengthened by real diamonds.



#### CLIMATEGUARD™ RESISTANCE

Resists extreme temperatures, allowing product to be used in 3-season spaces.

### TEST DATA

ASTM E492-09 Impact Sound Conduction & ASTM E90-09 Airborne Sound Conduction	6" slab, no drop ceiling (with IXPE): IIC 56 6" slab, no drop ceiling (with IXPE): STC 53
---	--

ASTM D2394 Slip Resistance DCOF (Sliding)	Dry: 0.69 Wet: 0.37
--	------------------------

NALFA LF 01-2019 Wear Resistance	AC4+, Light Commercial
-------------------------------------	------------------------

NALFA 3.2 Thickness Swell	Water Resistant
------------------------------	-----------------

ASTM D1037 Dynamic Load Limit	2,200 psi
----------------------------------	-----------

NALFA 3.1 Static Load Limit	8 MPA, Residential
--------------------------------	--------------------

NALFA 3.9 Caster Chair	25,000 cycles, no visible damage, Commercial
---------------------------	--

ASTM F2199-20 Dimensional Stability	Meets or Exceeds
--	------------------

ASTM E648 Critical Radiant Flux	Meets or Exceeds, No Delamination
------------------------------------	-----------------------------------

ASTM F1514-19 Resistance to Heat	Meets or Exceeds
-------------------------------------	------------------

ASTM F1515-21 Resistance to Light	Meets or Exceeds
--------------------------------------	------------------

NALFA 3.4 Resistance to Chemicals	No change, Not affected. Class 4, Commercial
--------------------------------------	--

ASTM D5824 Delamination Resistance	Meets or Exceeds, No Delamination
---------------------------------------	-----------------------------------

NALFA 3.10 Surface Bonding	Commercial
-------------------------------	------------

### WARRANTY



LIMITED RESIDENTIAL WARRANTY



LIMITED LIGHT COMMERCIAL WARRANTY

